

LIXUS® -i Systemreihe

Intelligente Zeilenkameras

Kamera	Option	Pixelanzahl	Pixelmaße [μm x μm]	aktive Länge [mm]	maximale Scanrate [Scans/s]	Anti-Bloom.	Shutter	Belichtungszeit		Objektivanschluß					Abmessungen [mm ³]
								min. [μs]	max. [ms]	C-Mount	F-Mount	Nikon	M72 x 1	Mamiya	
LIXUS-i 256	-59 -111	256	14 x 14	3,6	59.000 111.000	x	x	4,0 3,0	13 8,7	x	o	o	o	o	86 x 86 x 184
LIXUS-i 512	-32 -65	512	10 x 10	5,1	32.360 64.700	x	x	4,0 2,0	13 6,5	x	o	o	o	o	86 x 86 x 184
LIXUS-i 1024	-18 -35	1024	10 x 10	10,2	17.700 35.400	x	x	4,0 2,0	13 6,5	x	o	o	o	o	86 x 86 x 184
LIXUS-i 2048	-09 -19	2048	10 x 10	20,5	9.280 18.570	x	x	4,0 2,0	13 6,5		x	o	o	o	86 x 86 x 197
LIXUS-i 2048C		2048	14 x 14	28,7	2.380		x	5,0	105		x	o	o	o	86 x 86 x 197
LIXUS-i 4096	-05 -10	4096	10 x 10	40,96	4.757 9.514	x	x	4,0 2,0	13 6,5		x	o	o	o	86 x 86 x 197
LIXUS-i 5000		5000	7 x 7	35,0	1.580			630	131		x	o	o	o	86 x 86 x 197
LIXUS-i 5150		5150	7 x 7	36,1	5.630			180	70		x	o	o	o	86 x 86 x 197
LIXUS-i 6144		6144	7 x 7	43,0	4.810	x	x	3,0	70		x	o	o	o	86 x 86 x 197
LIXUS-i 7500		7500	7 x 7	52,5	3.900			260	70		o		x	o	86 x 86 x 212
LIXUS-i 7926		7926	7 x 7	55,5	990			1000	131		o		x	o	86 x 86 x 212
LIXUS-i 8192		8192	7 x 7	57,3	3.620	x	x	3,0	70		o		x	o	86 x 86 x 212

x – Standard o – Option

Technische Änderungen und Irrtum vorbehalten.